

[illegible][illegible]

925 481 004 0 (A) 925 481 050 0	925 481 006 0 (A) 925 481 051 0				
1:5	1:5				

A	925 481 006 0	-	7421401944	RELEASE POSITION	24/24	8,4	General Specifications: 4D-534-D Further Technical Notes: Doc. Code: General Tolerances: ISO-201 Range of Nominal Dimensions (± mm) Class I 0,5 1,0 50 180 400 Fin 0,5 1,0 5,0 15 2,0 Medium X 1,0 2,0 3,0 4,0 Coarse 2,0 3,5 5,0 6,5 Trapped Holes etc.: 4D-664-D 1) Tolerance Class Applied Crosshatched	Copyright WABCO® Date: 2009-05-06 Signature: Majewski 2009-05-26 Signature: Scapellato	WABCO	24/24	TRISTOP®-CYLINDER TRISTOP®-CYLINDER CYLINDRO-TRISTOP® CYLINDRO-TRISTOP®	
	925 481 004 0	-	7421401943	RELEASE POSITION	24/24	8,4						
	925 481 051 0	20522029	-	DRIVING POSITION	24/24	8,4						
	925 481 050 0	20522028	-	DRIVING POSITION	24/24	8,4						
WABCO	VOLVO		RENAULT	DELIVERY POSITION AMMUNITIONSTELLUNG POSIZIONE DI LIVRAISON POSIZIONE DI FORNITURA	TYPE TYPE TYPE TYPE	MASS GEWICHT MASSA MASSA (kg)	1	1	925 481 059 0	053	ML	1/1
	CUSTOMER'S NO. KUNDEN-NR.		IDENTIFICATION									
	No. CLIENT No. CLIENTE											